

Page: 1

Compilation date: 22/07/2014

# Section 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Product name: DYLON MACHINE FABRIC DYE DARK BROWN 350G Product code: MFD 11 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of substance / mixture: Domestic Fabric Dye. 350 g. 1.3. Details of the supplier of the safety data sheet Company name: SPOTLESS PUNCH LTD **Betchworth House** 57 - 65 Station Road Redhill Surrey RH1 1DL UK Tel: +44 (0)1737 781 300 Fax: +44 (0)1737 769 607 Email: consumer@spotlesspunch.co.uk 1.4. Emergency telephone number Emergency tel: +44 (0)1737 781 300 (office hours only) Section 2: Hazards identification 2.1. Classification of the substance or mixture Classification under CLP: Eye Irrit. 2: H319; Skin Sens. 1: H317 Classification under CHIP: Xi: R36; Sens.: R43 Most important adverse effects: May cause an allergic skin reaction. Causes serious eye irritation. 2.2. Label elements Label elements under CLP: Hazard statements: H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. Signal words: Warning Hazard pictograms: GHS07: Exclamation mark

Precautionary statements: P101: If medical advice is needed, have product container or label at hand.

### DYLON MACHINE FABRIC DYE DARK BROWN 350G

Page: 2

P280: Wear protective gloves.

P102: Keep out of reach of children.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT substance.

### Section 3: Composition/information on ingredients

### 3.2. Mixtures

### Hazardous ingredients:

### SODIUM CARBONATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
207-838-8	497-19-8	-	Eye Irrit. 2: H319	>75%
C.I. REACTIVE	YELLOW 27			
278-108-4	75199-00-7	-	Skin Sens. 1: H317	1-5%

### Non-hazardous ingredients:

### C.I. REACTIVE RED 123

EINECS	CAS	CHIP Classification	CLP Classification	Percent
273-401-3	68959-17-1	-	Resp. Sens. 1: H334; Skin Sens. 1: H317	<1%
C.I. REACTIVE	BLUE 225			
401-560-2	108624-00-6	-	Skin Sens. 1: H317	<1%

# Section 4: First aid measures

4.	1.	Descri	iption	of	first	aid	measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash
	immediately with plenty of soap and water.

### Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact.

### DYLON MACHINE FABRIC DYE DARK BROWN 350G

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Wash the spillage site with large amounts of water.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of dust in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

### DYLON MACHINE FABRIC DYE DARK BROWN 350G

Page: 4

### 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

Workplace exposure limits: No data available.

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Respiratory protection not required.
Hand protection:	Protective gloves. Gloves (alkali-resistant). Nitrile gloves. Rubber gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State:PowderColour:Pale brownOdour:Barely perceptible odourSolubility in water:Highly solublepH:11 (10g/L)

9.2. Other information

Other information: No data available.

### Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

### DYLON MACHINE FABRIC DYE DARK BROWN 350G

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: Contact with acids liberates toxic gas. In combustion emits toxic fumes of carbon

dioxide.

### Section 11: Toxicological information

### 11.1. Information on toxicological effects

### Hazardous ingredients:

### SODIUM CARBONATE

ORL	MUS	LD50	6600	mg/kg
ORL	RAT	LD50	4090	mg/kg
SCU	MUS	LD50	2210	mg/kg

### **C.I. REACTIVE YELLOW 27**

ORAL RAT LD50	>5000	mg/kg
---------------	-------	-------

### Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact. An itchy rash may occur at the
	site of contact.
Eye contact:	There may be irritation and redness. The eyes may water profusely.
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach
	pain may occur.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may
	cause coughing or wheezing.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.

### Section 12: Ecological information

### 12.1. Toxicity

### Hazardous ingredients:

### DYLON MACHINE FABRIC DYE DARK BROWN 350G

**Page:** 6

# Image: Image:

Other adverse effects: Negligible ecotoxicity.

### Section 13: Disposal considerations

SODIUM CARBONATE

13.1. Waste treatment methods			
Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal		
	company.		
Disposal of packaging:	Dispose of as normal industrial waste.		
NB:	The user's attention is drawn to the possible existence of regional or national		
	regulations regarding disposal.		

### Section 14: Transport information

Transport class: This product does not require a classification for transport.

### Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

### Section 16: Other information

### Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and 3:	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	R36: Irritating to eyes.
	R43: May cause sensitisation by skin contact.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive

### DYLON MACHINE FABRIC DYE DARK BROWN 350G

Page: 7