

Page: 1

Compilation date: 22/07/2014

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DYLON MACHINE FABRIC DYE WOODLAND BROWN 350G

Product code: MFD 17

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Domestic Fabric Dye. 350 g.

1.3. Details of the supplier of the safety data sheet

Company name: SPOTLESS PUNCH LTD

Betchworth House 57 - 65 Station Road

Redhill Surrey RH1 1DL UK

Tel: +44 (0)1737 781 300 Fax: +44 (0)1737 769 607

Email: consumer@spotlesspunch.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1737 781 300

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; -: EUH208

Classification under CHIP: Xi: R36

Most important adverse effects: Causes serious eye irritation. Contains c.i. reactive blue 225, c.i. reactive black 5, c.i.

reactive red 123. May produce an allergic reaction.

2.2. Label elements

Label elements under CLP:

Hazard statements: H319: Causes serious eye irritation.

EUH208: Contains c.i. reactive blue 225, c.i. reactive black 5, c.i. reactive red 123. May

produce an allergic reaction.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



DYLON MACHINE FABRIC DYE WOODLAND BROWN 350G

Page: 2

Precautionary statements: P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P280: Wear protective gloves.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM CARBONATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
207-838-8	497-19-8	-	Eye Irrit. 2: H319	25-50%

Non-hazardous ingredients:

C.I. REACTIVE BLACK 5

_					
EINECS	CAS	CHIP Classification	CLP Classification	Percent	
241-164-5	17095-24-8	-	Resp. Sens. 1: H334; Skin Sens. 1: H317	<1%	
C.I. REACTIVE BLUE 225					
401-560-2	108624-00-6	-	Skin Sens. 1: H317	<1%	

~ 1		CTIVE	DED	122
\ /. I.	Γ		NLD	1/0

273-401-3	68959-17-1	-	Resp. Sens. 1: H334; Skin Sens. 1:	<1%
			H317	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

DYLON MACHINE FABRIC DYE WOODLAND BROWN 350G

Page: 3

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

DYLON MACHINE FABRIC DYE WOODLAND BROWN 350G

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Hand protection: Protective gloves. Gloves (acid resistant). Nitrile gloves. Rubber gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Powder

Colour: Pale brown

Odour: Barely perceptible odour

Solubility in water: Highly soluble

pH: 11 (10g/L)

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: Contact with acids liberates toxic gas. In combustion emits toxic fumes of carbon

dioxide.

DYLON MACHINE FABRIC DYE WOODLAND BROWN 350G

Page: 5

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM CARBONATE

ORL	MUS	LD50	6600	mg/kg
ORL	RAT	LD50	4090	mg/kg
SCU	MUS	LD50	2210	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM CARBONATE

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

DYLON MACHINE FABRIC DYE WOODLAND BROWN 350G

Page: 6

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

R36: Irritating to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.