

Page: 1

Compilation date: 20/10/2014

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DYLON MACHINE FABRIC DYE BAHAMA BLUE 350G

Product code: MFD 21

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Domestic Fabric Dye. 350 g.

1.3. Details of the supplier of the safety data sheet

Company name: SPOTLESS PUNCH LTD

Betchworth House 57 - 65 Station Road

Redhill Surrey RH1 1DL UK

Tel: +44 (0)1737 781 300 Fax: +44 (0)1737 769 607

Email: consumer@spotlesspunch.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1737 781 300

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319

Classification under CHIP: Xi: R36/38; Sens.: R43

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Label elements under CLP:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



DYLON MACHINE FABRIC DYE BAHAMA BLUE 350G

Page: 2

Precautionary statements: P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P280: Wear protective gloves/eye protection.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM CARBONATE

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|-----------------------|------------|---------------------|---|---------|
| 207-838-8 | 497-19-8 | - | Eye Irrit. 2: H319 | 25-50% |
| DISODIUM METASILICATE | | | | |
| 229-912-9 | 6834-92-0 | - | Skin Corr. 1B: H314; STOT SE 3: H335 | 5-10% |
| C.I. REACTIVE | BLUE 116 | | | |
| 276-012-7 | 71786-55-5 | - | Skin Sens. 1: H317; Aquatic Chronic | 1-5% |

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact. An itchy rash may occur at the

site of contact.

Eye contact: There may be irritation and pain. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

DYLON MACHINE FABRIC DYE BAHAMA BLUE 350G

Page: 3

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of dust in

the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

DYLON MACHINE FABRIC DYE BAHAMA BLUE 350G

Page: 4

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Hand protection: Protective gloves. PVC gloves. Butyl gloves. Nitrile gloves. Rubber gloves. Gloves

(alkali-resistant).

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Powder

Colour: Turquoise

Odour: Characteristic odour

Solubility in water: Highly soluble

Flash point°C: Not applicable.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Humidity.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide.

DYLON MACHINE FABRIC DYE BAHAMA BLUE 350G

Page: 5

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM CARBONATE

| ORL | MUS | LD50 | 6600 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 4090 | mg/kg |
| SCU | MUS | LD50 | 2210 | mg/kg |

DISODIUM METASILICATE

| ORL | MUS | LD50 | 770 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 1153 | mg/kg |

C.I. REACTIVE BLUE 116

| ORL | RAT | LD50 | > 2000 | mg/kg |
|-----|-------|------|--------|---------|
| OIL | 13/51 | LD30 | / 2000 | 111g/kg |

Relevant effects for mixture:

| Effect | Route | Basis |
|---------------|---------|-----------------------|
| Irritation | OPT DRM | Hazardous: calculated |
| Sensitisation | DRM | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. An itchy rash may occur at the

site of contact.

Eye contact: There may be irritation and pain. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM CARBONATE

DYLON MACHINE FABRIC DYE BAHAMA BLUE 350G

Page: 6

DISODIUM METASILICATE

C.I. REACTIVE BLUE 116

| - | IC50 | > 100 | mg/l |
|---------------|----------|----------|------|
| RAINBOW TROUT | 96H LC50 | 10 - 100 | mg/l |

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

DYLON MACHINE FABRIC DYE BAHAMA BLUE 350G

Page: 7

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.